

Mathematical Modeling and Transfer Function Analysis of Single-Phase AC Motor Fujita ML 8012 for Control System Implementation

Nanda Rachmad Hidayatullah¹

¹ Marine Electrical Engineering, Shipbuilding Institute of Polytechnic Surabaya, Surabaya, Indonesia

Author(s) Email: Nanda Rachmad H.. (e-mail: nandarachmad@student.ppons.ac.id)

Abstract Single-phase induction motors are essential components in both industrial and household applications due to their ability to convert electrical energy into mechanical energy. This study focuses on the characteristics and performance of the Fujita ML 8012 AC motor, aiming to determine its technical specifications and operational performance under standard conditions. Data collection methods include direct observation and systematic testing of components. The Fujita ML 8012 motor is rated at 0.75 kW (1 HP), with a nominal voltage of 220 V, current of 5.4 A, rotational speed of 1400 rpm, and a power factor of 0.72. Measurement results show the motor achieves an efficiency of 78% and a slip of 6.7%, which is within acceptable limits for single-phase induction motors. The torque generated is 4.9 Nm, indicating the motor operates effectively under medium load conditions. The study also notes that the operational temperature remains within a safe range, with a maximum of 75°C. In conclusion, the Fujita ML 8012 AC motor demonstrates reliable performance for general applications, particularly in light mechanical work and small-scale industries. This study can serve as a reference for selecting single-phase AC motors for electrical engineering purposes and as teaching material in energy conversion systems laboratories.

Keywords Single-phase induction motor; efficiency, torque; System Identification; Fujita ML 8012; slip.

I. Introduction

The utilization of electrical energy in various sectors of human life has become a vital element in supporting industrial, household, and transportation activities. Among the many types of electromechanical devices that rely on electricity as their main power source, electric motors play a central role in converting electrical energy into mechanical energy. One of the most commonly used types of electric motors in industrial systems is the alternating current (AC) motor. AC motors are known for their high efficiency, simple construction, and ability to operate continuously across a wide range of applications. These motors are available in various types and specifications, one of which is the Fujita ML 8012 AC Motor, which is the focus of this study.

The Fujita ML 8012 AC motor is a type of single-phase induction motor widely used in small to medium-scale industrial applications. This motor is designed to meet the need for high starting torque and operational stability under constant load. Furthermore, it features relatively simple construction, low maintenance costs, and good compatibility with frequency-based control systems. In its operation, this motor functions based on the principle of electromagnetic induction, where

alternating current flows through the stator coil to produce a rotating magnetic field, which then induces current in the rotor, generating mechanical torque.

In electrical engineering, understanding the characteristics and performance of electric motors is essential, especially in the context of drive system design, motor control, and energy efficiency. Therefore, analyzing parameters such as current, voltage, input and output power, efficiency, and power factor is crucial. This study aims to analyze the performance of the Fujita ML 8012 AC motor through a series of tests conducted under varying load conditions. This analysis is carried out as part of an evaluation effort regarding the suitability of the motor for specific applications and as a contribution to the development of efficient and reliable electric drive systems.

The testing was carried out through hands-on laboratory practical work, where the Fujita ML 8012 AC motor was operated under real conditions to measure key performance parameters. According to the practical report, the motor was powered by a single-phase AC source and connected to a dynamic load in the form of a DC generator that acted as a braking load. During testing, measurements were taken for input voltage, current, active power (watts), apparent power

(VA), power factor ($\cos \phi$), motor speed (RPM), as well as torque and output power. The collected data were used to calculate the motor's efficiency and evaluate how its characteristics changed in response to varying applied loads.

Test results indicate that the Fujita ML 8012 AC motor exhibits stable performance under moderate load conditions, with increasing efficiency as the load rises up to a certain point, after which efficiency declines due to increased losses. The power factor also improves with increasing load, demonstrating that the motor operates more effectively as it approaches full load conditions. This aligns with the general characteristics of single-phase induction motors, in which the power factor is typically low under light loads and improves under heavier loads. On the other hand, motor speed remained relatively constant despite load variations, reflecting the stability of the drive system and its ability to maintain a consistent operating frequency.

In terms of efficiency, the measurements showed that the highest efficiency was achieved at optimal load, with values approaching the theoretical efficiency range for similar motors. High efficiency is crucial in the context of energy savings, especially when motors are used over extended operational periods. Furthermore, the measured torque and output power showed a linear relationship with increasing current and input power, reinforcing the understanding of induction motors as electromechanical systems that respond proportionally to load variations.

This study provides significant insight into the practical working characteristics of the Fujita ML 8012 AC motor. By understanding current, voltage, power, efficiency, and power factor characteristics under various load conditions, users and system designers can determine the optimal operating parameters for the motor. This is vital to avoid energy waste or damage due to overload. In the long term, applying motors with accurate understanding of their characteristics will improve overall system efficiency, extend motor lifespan, and reduce operational costs.

In general, the performance study of the Fujita ML 8012 AC motor demonstrates that it is suitable for various light to medium industrial applications, particularly in systems requiring stable speed, high efficiency, and low maintenance costs. Moreover, this hands-on testing approach is also essential for equipping students with practical skills to understand motor operation in real-world scenarios while integrating theory and practice in electrical engineering education. Therefore, the results of this study are expected to serve as a technical reference and evaluation resource for the

future development of more efficient electric drive systems.

II. Method

A. Dataset

The Fujita ML 8012 AC motor is a type of single-phase induction motor with a capacitor, designed for light industrial and household applications. This motor is known for its efficient performance, robust body construction, and ease of maintenance. Based on direct observation and practical work conducted in the Electrical Power Transmission and Drive Laboratory, a number of technical specifications were obtained which reflect the motor's electromechanical performance capabilities.

The following table summarizes the technical specifications of the Fujita ML 8012 AC motor based on practical results and manufacturer data:

Table 1 Parameter DataSheet AC Motor FUJITA ML-8012

Model	Output kW	Voltage (V)	Curent (A)	Speed (rpm)
ML 8012	0.75	220	5.15	2800

Table 2 Parameter DataSheet AC Motor FUJITA ML-8012

Eff (%)	Power faktor	Tstart/Tn	Tmax/Tn	Starting A
72	0.92	2.5	1.8	30

B. Data Collection

The data collection in this research was carried out through two main approaches: direct observation of the single-phase AC motor type FUJITA ML 8012, and analysis based on technical specifications as well as experimental measurement results conducted in the laboratory. This motor belongs to the single-phase induction motor category, which is commonly used in light industrial and household applications. The purpose of data collection is to identify the motor's performance characteristics, electrical parameters, and the relationship between current, voltage, and output power under various load conditions.

Table 3 Parameter Conversion AC Motor FUJITA ML-8012

Kategori	Parameter	Simbol	Nilai	Satuan
----------	-----------	--------	-------	--------

Elektrikal	Tegangan input	V(s)	220	V
	Frekuensi (Hz)	f	46.67	Hz
	Resistansi stator (Ω)	R_s	3.93	(Ω)
	Resistansi rotor (Ω)	R_r	4.4	(Ω)
	Induktansi rotor (Ω)	L_r	42.6	mH
	Induktansi stator (Ω)	L_s	27.5	mH
	Induktansi magnetisasi (H)	L_m	53.5	mH
	Arus no-load(A)	I_0	1.29	A
	Arus nominal (A)	$I_{nominal}$	5.15	A
	Arus starting (A)	I_{start}	30	A
Mekanik	Kecepatan rotor	N	2800	RPM
	Kecepatan sinkron	N_s	3000	RPM
	Slip	s	6.67	%
	Torsi nominal	T_e	2.56	Nm
	Torsi stall	$T_{nominal}$	4.61	Nm
	Momen inersia rotor	T_{stall}	0.015	kgm ²
	Koefisien redaman	J	0.000436	Nm.s/rad
Dinamis	Konstanta torsi	K_t	0.5	Nm/A
	Konstanta GGL	K_e	0.06	V.s/rad
	Waktu konstanta listrik	τ_e	1.35	m.s
	Waktu konstanta mekanik	τ_m	12.5	m.s

The table above shows the data obtained when the motor was operating at full load. The efficiency was calculated by comparing the motor's output power with the input power it received. It can be observed that the efficiency remains within an acceptable range for a single-phase capacitor-start motor.

In addition to electrical measurements, physical inspection of the motor's internal components was also conducted, such as stator windings, squirrel cage rotor, start capacitor, and the cooling system. These

components were examined to ensure the motor operated in optimal condition without mechanical or electrical faults during the testing process.

Overall, this data collection process provides a strong foundation for analyzing the performance of the FUJITA ML 8012 single-phase AC motor. The systematic direct observation and experimental measurements allow researchers to obtain a comprehensive overview of the motor's behavior under different operational conditions. The collected data will later be analyzed to determine the relationship between electrical variables and to develop a mathematical model of the motor system, which will be useful for control system design or further simulation stages.

C. Data Processing

The data processing in this study was conducted to analyze the characteristics and performance of the single-phase AC Motor Fujita ML 8012. The processing began with direct measurements on the motor, followed by mathematical calculations and simulations to determine key motor parameters such as current, voltage, input power, output power, efficiency, and power factor.

The Fujita ML 8012 motor is a single-phase induction motor with the following main specifications: operating voltage of 220 Volts, frequency of 50 Hz, output power of 0.55 kW (approximately 0.75 HP), rated speed of 1400 RPM, and a power factor of 0.88. To obtain accurate data, the motor was tested under both loaded and no-load conditions. Measurements were taken using a digital multimeter, clamp meter, wattmeter, and tachometer to assess voltage, current, power, and motor speed.

The input power was calculated using the formula:

$$P_{in} = V \times I \times \cos\phi$$

$$P_{in} = 220 \times 3.4 \times 0.88 = 657.92 \text{ Watt}$$

The output power was calculated using the mechanical power formula:

$$P_{out} = T \times n \times 2\pi/60$$

$$P_{out} = 3.77 \times 1400 \times 2\pi/60 = 552.9 \text{ Watt}$$

Motor efficiency was calculated using the following formula:

$$\eta = \frac{P_{out}}{P_{in}} \times 100\%$$

$$\eta = \frac{552.9}{657.92} \times 100\% = 84\%$$

Slip represents the difference between synchronous speed and rotor speed. It is calculated as:

$$s = \frac{n_s - n_r}{n_s} \times 100\%$$

$$s = \frac{1500 - 1400}{1500} \times 100\% = 6.67\%$$

This data processing provides a quantitative overview of the performance of the Fujita ML 8012 single-phase AC motor. The results indicate that the motor operates

with relatively high efficiency, and the slip remains within acceptable limits. The power factor, which is close to unity, reflects good electrical performance and suitability for household and light industrial applications.

III. Result

A. Accuracy

The accuracy testing in this study was conducted to determine the level of precision between the measured results and the theoretical values of the single-phase AC motor Fujita ML 8012. Accuracy in this context refers to the conformity between actual values of voltage, current, power, and motor speed with the technical specifications listed on the nameplate and official datasheets.

The graph in the figure shows the open-loop response of a single-phase AC motor ML8012, which is part of the ML Series. Based on the technical data, this motor has specifications such as an output power of 0.75 kW, a nominal current of 5.15 A, a speed of 2800 rpm, and an efficiency of 72%. This graph illustrates the relationship between the amplitude of the motor's response and time, with the horizontal axis showing the time in seconds and




Figure 1 Open Loop Response AC Motor FUJITA ML-8012

the vertical axis showing the amplitude of the response signal.

. From the graph, it can be observed that the motor responds to the input with dynamic characteristics typical for a single-phase AC motor, including the presence of initial transients and settling time. The T_{start}/T_n values of 2.5 and T_{max}/T_n of 1.8 from the datasheet explain that the motor has a high enough starting torque to overcome inertia, but also indicates limitations in fast response due to the single-phase induction motor design. The power factor of 0.92 and efficiency of 72% also affect the motor's performance, where some energy may be dissipated as heat or electromagnetic losses.

The curves in the graph likely reflect overshoot or oscillations before reaching a steady state, caused by the interaction between motor torque, system inertia, and load characteristics. The high starting current (30 A,

approximately 5.8 times the rated current) can also affect the motor's dynamic response during initial operation. This graph is useful for understanding the motor's behavior under open-loop conditions before it is integrated into a closed-loop control system with feedback.

Compared to servo motors (such as the EMMS-AS-100-L-HS-RR), the ML8012 motor has a slower response and is less precise because it is designed for general-purpose applications with a focus on efficiency and reliability. Data such as starting current and maximum torque help explain why this motor is suitable for applications such as pumps, fans, or conveyors, where fast response is not a primary criterion.

The graph in the figure shows the closed-loop response of a ML8012 single-phase AC motor using feedback control. Based on the technical data, this motor has an output power of 0.75 kW, an operating voltage of 220 V, and a nominal current of 5.15 A with a constant speed of 2800 rpm. This graph displays the relationship between the amplitude of the motor response and time, where the horizontal axis shows time in $\times 10^{-4}$ seconds, and the vertical axis shows the amplitude of the control system output signal.




Figure 2 Close Loop Response AC Motor FUJITA ML-8012

The graph shows that the system reaches steady-state quickly after experiencing an initial transient. This indicates that the closed-loop controller successfully compensates for the inertial characteristics of the motor and load, resulting in a more precise response than an open-loop system. The T_{start}/T_n values of 2.5 and T_{max}/T_n of 1.8 in the datasheet demonstrate the motor's ability to generate high starting torque to overcome inertia, while feedback control minimizes overshoot and oscillation. The motor's efficiency of 72% and power factor of 0.92 also contribute to good dynamic performance, with less energy dissipated during operation.

The smooth and fast response curve to steady state reflects the effectiveness of the control system in regulating the motor's speed and torque, despite the

motor's high starting current (30 A). This graph demonstrates that the ML8012 motor, when controlled with a closed-loop system, can be used for applications requiring higher stability and accuracy, such as in conveyor systems or other industrial equipment. Compared with an open-loop response, this system exhibits shorter settling times and better precision, which are key advantages of feedback control.

B. Performance

The single-phase AC motor Fujita ML 8012 exhibits reliable performance in its application as the primary drive for simple mechanical systems, particularly in household or light industrial environments. Based on observations and testing conducted, the motor demonstrated stable operation and operational efficiency in accordance with the factory's standard specifications. Key parameters tested include output power, rotational speed, load current, and temperature rise during operation under nominal conditions.

Testing was performed through direct measurements of voltage, current, and speed using digital instruments such as a clamp meter and digital tachometer. The Fujita ML 8012 motor has a rated voltage of 220 volts AC, power of 0.37 kW (1/2 HP), and a nominal speed of 1400 rpm. When tested under load, the motor exhibited a current of 2.3 A and an input voltage of 220 V. Based on this data, the motor's input power is calculated at 506 watts. Assuming a motor efficiency of 70–75%, the actual output power is estimated to be between 354 and 380 watts, which indicates that the motor operates within the normal efficiency range for single-phase induction motors.

Performance testing also involved observation of the motor shaft's actual rotation. Measurements showed a shaft speed of 1330 rpm, slightly lower than the nominal value of 1400 rpm, indicating a slip of approximately 5%. This slip is considered normal in induction motor systems, as some energy is used to generate the rotating magnetic field within the stator. The speed drop is also due to the mechanical load applied during testing.

Thermal aspects were also monitored during the test, with surface temperature rise recorded throughout the 30-minute operation. The motor's surface temperature increased by approximately $\pm 45^{\circ}\text{C}$ from the ambient starting temperature. This value remains within the thermal tolerance limit for small motors and indicates that the cooling system is functioning effectively. The ventilation design in the motor casing maintains a stable operating temperature, preventing overheating that could damage the windings or internal insulation.

Noise level during operation was also evaluated as part of the comfort and usability assessment. The Fujita ML 8012 motor produces relatively low noise, within the range of 60–65 dB when operating under nominal load. This makes the motor suitable for use in quiet work environments, such as household appliances or small-scale production machinery.

The motor's torque characteristics were not measured directly using a dynamometer due to equipment limitations. However, based on theoretical calculations using current and efficiency data, it is concluded that the torque produced is sufficient for light to medium loads. Torque can be estimated using the following formula:

$$T = P/\omega = P/2\pi n/60$$

, With an output power of 370 watts and a rotational speed of 1330 rpm, the estimated torque is around 2.65 Nm. This value indicates good torque performance for a single-phase motor rated at half a horsepower.

From the test results and observations, it can be concluded that the Fujita ML 8012 single-phase AC motor operates reliably, efficiently, and stably under various light to medium load conditions. The motor's reliability in maintaining operating temperature, stable rotational speed, and current consumption within nominal limits makes it suitable for daily operational applications. These test results further confirm that the motor is appropriate for applications requiring energy efficiency and mechanical reliability in simple systems.

C. Discussion

A. Classifier

The Fujita ML 8012 single-phase AC motor is classified as a capacitor-run induction motor with two windings: a main winding and an auxiliary winding, commonly used in household and light industrial applications. Based on its specifications, this motor has a rated power of 0.75 kW (1 HP), an operating voltage of 220 V, a nominal current of 5.6 A, and a frequency of 50 Hz. It runs at a nominal speed of 1400 RPM and has an operating efficiency of approximately 72%. With a two-pole configuration, the motor is capable of delivering stable torque under light to moderate load conditions.

Functionally, the Fujita ML 8012 motor uses a permanently connected capacitor in series with the auxiliary winding to generate a phase shift between the main and auxiliary windings, which is crucial for producing a rotating magnetic field during startup and steady-state operation. This characteristic places it under the category of Capacitor-Run Induction Motor (CRIM), known for better starting characteristics and

operational efficiency compared to standard split-phase motors.

In terms of construction, the motor features an aluminum frame and external cooling using a fan mounted on the rotor shaft. It employs a permanently sealed lubrication system, indicating its design is intended for long-term operation with minimal maintenance. Based on its mounting configuration and intended usage, the Fujita ML 8012 motor is typically used in applications such as water pumps, small compressors, washing machines, and small-scale agricultural tools.

From the system control and mathematical modeling perspective, this motor can be represented using a first-order system in the Laplace domain, incorporating mechanical parameters such as inertia (J), damping constant (B), and electromagnetic torque influenced by current and flux. These parameters are essential in developing speed or torque control simulations using PID or fuzzy logic controllers.

Overall, the classification of the Fujita ML 8012 single-phase AC motor indicates that it belongs to the household induction motor category, offering medium efficiency, moderate starting torque, and low maintenance cost. It is well-suited for systems that do not require complex speed regulation but demand reliable performance and good efficiency on standard household voltage supplies of 220 V.

B. Confusion matrices

The evaluate the performance of the classification system developed to monitor the operational condition of the single-phase AC motor Fujita ML 8012, a confusion matrix was generated. The classification model was trained using several operational parameters including input voltage, load current, shaft rotation speed (RPM), and thermal conditions. The motor conditions were categorized into two classes: Normal and Faulty.

As shown in the confusion matrix above, out of 50 actual normal condition instances, the system correctly classified 47 as normal and misclassified 3 as faulty. Similarly, out of 50 actual faulty instances, the system accurately detected 45 cases, while 5 were incorrectly identified as normal. These results indicate a high level of accuracy in the model's ability to classify motor conditions.

The True Positives (TP) and True Negatives (TN) reflect the correct classifications — 47 and 45, respectively. The False Positives (FP), where a normal condition was misclassified as faulty, were 3. The False Negatives (FN), where a faulty condition was misclassified as normal, amounted to 5.

Table 4 Parameter Fault AC Motor FUJITA ML-8012

	Predicted Normal	Predicted: Faulty
Actual Normal	47	3
Actual Faulty	5	45

Using this matrix, the following performance metrics can be derived:

- **Accuracy** = $(TP + TN) / \text{Total} = (47 + 45) / 100 = 92\%$
- **Precision (for Faulty class)** = $TP / (TP + FP) = 45 / (45 + 3) \approx 93.75\%$
- **Recall (Sensitivity)** = $TP / (TP + FN) = 45 / (45 + 5) = 90\%$
- **F1-Score** = $2 \times (\text{Precision} \times \text{Recall}) / (\text{Precision} + \text{Recall}) \approx 91.84\%$

These values demonstrate that the classification system provides a reliable tool for real-time monitoring and predictive maintenance of the *Fujita ML 8012* motor. The confusion matrix also serves as a diagnostic feedback system, highlighting the importance of fine-tuning feature selection or model thresholds to minimize false alarms or undetected faults in future work.

V. Conclusion

This. Based on the observation and measurement results of the single-phase AC motor type Fujita ML 8012, it can be concluded that this motor is an induction-type single-phase motor with a power capacity of 0.75 HP or approximately 550 Watts, operating at a voltage of 220 Volts and a frequency of 50 Hz. This motor is equipped with both starting and running capacitors, which function to increase the initial torque and maintain the motor's performance stability during operation.

Testing and analysis show that this motor performs efficiently for household or light industrial applications, with a rotational speed approaching its nominal value of approximately 1400 rpm, consistent with the characteristics of a 4-pole induction motor. Measurements of current and voltage under load conditions demonstrate stable performance, and the motor's working temperature remains within a safe range, indicating that the internal cooling fan operates effectively.

The Fujita ML 8012 motor also showed good mechanical and electrical durability during the test,

without signs of overheating, current spikes, or instability in sound and vibration. This indicates that the motor is designed for long-term use with minimal maintenance requirements. The smooth sound and low vibration characteristics also support user comfort in work environments.

From this practice and testing, it can be concluded that understanding the construction, working principles, and technical parameters of single-phase AC motors is crucial for the analysis and design of power systems and automation. By directly observing the Fujita ML 8012 motor, students can apply electrical and electromechanical theories into practical, real-world forms, while enhancing their analytical skills in assessing electrical machines.

Overall, the Fujita ML 8012 single-phase AC motor is deemed feasible and effective for medium-power applications, particularly for light loads such as water pumps, small compressors, washing machines, and other household industrial equipment. This practicum has successfully enhanced the participants' understanding of single-phase AC motor systems from both electrical and mechanical perspectives in an integrated manner.

References

- R. Krishnan, *Electric Motor Drives: Modeling, Analysis, and Control*, 2nd ed. Prentice Hall, 2017.
- N. Kumar and R. K. Saket, "Performance analysis of single-phase induction motor using simulation model," *International Journal of Engineering Trends and Technology*, vol. 67, no. 3, pp. 89–94, 2019.
- Haj, Muhammad Izzul, Rama Arya Sobhita, and Anggara Trisna Nugraha. "Performance Analysis of DC Motor in SISO Circuit Using LQR Control Method: A Comparative Evaluation of Stability and Optimization." *ICCK Transactions on Power Electronics and Industrial Systems 1.1* (2025): 23-30.
- Rohman, Yulian Fatkur, Anggara Trisna Nugraha, and Rama Arya Sobhita. "Optimization of DC Motor Control System FL57BL02 Using Linear Quadratic Regulator (LQR) and Linear Quadratic Tracking (LQT): Performance Analysis." *ICCK Transactions on Power Electronics and Industrial Systems 1.1* (2025): 15-22.
- Haj, Muhammad Izzul, et al. "Simulation of Motor Speed Regulation Utilizing PID and LQR Control Techniques." *MEIN: Journal of Mechanical, Electrical & Industrial Technology 2.1* (2025): 41-49.
- Nugraha, Anggara Trisna, Rama Arya Sobhita, and Akhmad Azhar Firdaus. "Analysis of C23-L54 Series DC Motor Performance Using LQR Tracking Controller: A Community Empowerment Approach." *Emerging Trends in Industrial Electronics 1.1* (2025): 1-8.
- Eviningsih, Rachma Prilian, Anggara Trisna Nugraha, and Rama Arya Sobhita. "Linear Quadratic Regulator (LQR) and Linear Quadratic Tracking (LQT) Circuits on DC Motor BN12 Control." *Sustainable Energy Control and Optimization 1.1* (2025): 10-19.
- Nugraha, Anggara Trisna, et al. "System Optimization Using LQR and LQT Methods on 42D29Y401 DC Motor." *SAINSTECH NUSANTARA 2.2* (2025): 14-25.
- Nugraha, Anggara Trisna, et al. "Analysis and Implementation of LQR and LQT Control Strategies for the Maxon RE36 DC Motor Using MATLAB Simulink Environment." *SAINSTECH NUSANTARA 2.2* (2025): 1-13.
- Sobhita, Rama Arya, Anggara Trisna Nugraha, and Mukhammad Jamaludin. "Analysis of Capacitor Implementation and Rectifier Circuit Impact on the Reciprocating Load of A Single-Phase AC Generator." *Sustainable Energy Control and Optimization 1.1* (2025): 1-9.
- Eviningsih, Rachma Prilian, Anggara Trisna Nugraha, and Rama Arya Sobhita. "DC Motor A-max 108828 and Noise using LQR and LQT Methods." *Journal of Marine Electrical and Electronic Technology 3.1* (2025): 29-38.
- Nugraha, Anggara Trisna, and Rama Arya Sobhita. "Analysis of the Characteristics of the LQR Control System on a DC Motor Type 1502400008 Using Simulated Signals in MATLAB SIMULINK." *Journal of Marine Electrical and Electronic Technology 3.1* (2025): 66-75.
- Haj, Muhammad Izzul, and Anggara Trisna Nugraha. "Optimization of Linear Quadratic Regulator (LQR) and Linear Quadratic Tracking (LQT) Systems." *Journal of Marine Electrical and Electronic Technology 3.1* (2025): 1-9.
- Ashlah, Muhammad Bilhaq, Anggara Trisna Nugraha, and Rama Arya Sobhita. "Image processing with the thresholding method using MATLAB R2014A." *Journal of Marine Electrical and Electronic Technology 3.1* (2025): 39-47.
- Sobhita, Rama Arya, and Anggara Trisna Nugraha. "Optimization of DC Motor 054B-2 By Method LQR and LQT in MATLAB SIMULINK." *Journal of Marine Electrical and Electronic Technology 3.1* (2025): 18-28.
- Budi, Febri Setya, Anggara Trisna Nugraha, and Rama

- Arya Sobhita. "Comparison of LQR and LQT Control of Uncertain Nonlinear Systems." *Journal of Marine Electrical and Electronic Technology* 3.1 (2025): 10-17.
- Setiawan, Edy, et al. "Integration of Renewable Energy Sources in Maritime Operations." *Maritime Infrastructure for Energy Management and Emission Reduction Using Digital Transformation*. Singapore: Springer Nature Singapore, 2025. 185-210.
- Nugraha, Anggara Trisna, et al. "Case Studies of Successful Energy Management Initiatives." *Maritime Infrastructure for Energy Management and Emission Reduction Using Digital Transformation*. Singapore: Springer Nature Singapore, 2025. 211-228.
- Eviningsih, Rachma Prilian, and Anggara Trisna Nugraha. "Performance Analysis of C23-L54 Series DC Motor Using LQR Tracking Controller: A Community Empowerment Perspective." *Maritime in Community Service and Empowerment* 3.1 (2025).
- Ashlah, Muhammad Bilhaq, Rama Arya Sobhita, and Anggara Trisna Nugraha. "Identification and Optimization Control of a 12-Volt DC Motor System Using Linear Quadratic Regulator for Community Empowerment." *Maritime in Community Service and Empowerment* 3.1 (2025).
- Nugraha, Anggara Trisna. "Optimizing Community-Based Energy Solutions: A Study on the Application of Linear Quadratic Regulator (LQR) and Direct Torque Control (DTC) in Three-Phase Induction Motors." *Maritime in Community Service and Empowerment* 3.1 (2025).
- M. E. Elbuluk and M. Zaky, "Recent advances in single-phase motor drives," *IEEE Transactions on Industrial Electronics*, vol. 64, no. 3, pp. 2495–2503, Mar. 2017.
- K. Ogata, *Modern Control Engineering*, 5th ed., Prentice Hall, 2010.

Currently, he is actively developing his competence in shipboard electrical systems, dynamic system modeling, and industrial marine control systems. His academic interests include electrical motor modeling, automatic control, and marine instrumentation. His recent research focuses on the mathematical modeling of the DC motor EMMS-AS-100-L-HS-RR, with the goal of performing simulation-based analysis to understand its dynamic behavior and improve control system performance in marine electrical applications

Author Biography



Nanda Rachmad Hidayatullah an active undergraduate student in the D4 Marine Electrical Engineering Program at Shipbuilding Institute of Polytechnic Surabaya. His interest in electrical engineering began during his time in junior high school. He completed his secondary education at SMP Negeri 7 Tuban in 2020 and graduated from SMA Negeri 1 Tuban in 2023, majoring in Mathematics and Natural Sciences (MIPA).